

RT615



(35-60 SERIES) STEEL BELTED
(SERIES 35-60) BANDA DE RODADURA REFORZADA CON ACERO

- Pure sport performance tires, built to AZENIS RT specs.
- Motorsport-grade cap compound maintains its grip over a wide range of operating temperatures.
- Enhanced wet grip and aquaplane resistance under competition conditions.
- *Neumáticos de rendimiento deportivo con especificaciones AZENIS RT.*
- *El compuesto de la tapa del grado Motorsport mantiene un excelente agarre sobre una amplia gama de las temperaturas de trabajo.*
- *Mejor agarre en estado húmedo y resistencia al acuaplano bajo las condiciones de competición.*

Size	Load Index & Speed Symbol	RF	TL	E-NO.	Rim Width		Overall Diameter (mm)	Section Width (mm)	Static Loaded Radius $\pm 1.5\%$ (mm)	Rolling Circumference $\pm 2.0\%$ (mm)	Tread Depth (mm)
					Approved (Inch)	Measuring (Inch)					
275 / 35 R 18	95W		TL	MFS	9.0 - 11.0	9.5	651	274	533	1986	6.3
205 / 40 R 16	83W		TL	MFS	7.0 - 8.0	7.5	572	217	471	1745	6.3
205 / 40 R 17	84W		TL	MFS	7.0 - 8.0	7.5	595	217	495	1815	6.3
215 / 40 R 17	87W		TL	MFS	7.0 - 8.5	7.5	606	221	500	1848	6.3
255 / 40 R 17	94W		TL	MFS	8.5 - 10.0	9.0	634	260	511	1934	6.3
275 / 40 R 17	98W		TL	MFS	9.0 - 11.0	9.5	650	275	517	1983	6.3
225 / 40 R 18	92W		TL	MFS	7.5 - 9.0	8.0	638	236	528	1946	6.3
235 / 40 R 18	95W		TL	MFS	8.0 - 9.5	8.5	648	243	532	1976	6.3
245 / 40 R 18	97W		TL	MFS	8.0 - 9.5	8.5	652	249	533	1989	6.3
255 / 40 R 18	95W		TL	MFS	8.5 - 10.0	9.5	660	260	536	2013	6.3
225 / 45 R 17	94W		TL	MFS	7.0 - 8.5	7.0	636	225	511	1940	6.3
245 / 45 R 17	99W		TL	MFS	7.5 - 9.0	8.0	652	243	518	1989	6.3
225 / 45 R 18	91W		TL	MFS	7.0 - 8.5	7.5	657	227	535	2004	6.3
205 / 50 R 15	89W		TL	MFS	5.5 - 7.5	6.5	591	209	463	1803	6.3
195 / 60 R 14	86H		TL		5.5 - 7.0	6.0	590	200	447	1800	6.3

RF: Reinforced tires *Neumáticos reforzados*

TL: Tubeless tires *Neumáticos sin cámara*

MFS: Max flange shield (Rim protection feature)